

ISO tumble dryer

Model: YG743



Brand & Origin: Sanxin, Hongkong.

Instructions: the scope of use It is used for drying all kinds of textiles after shrinkage experiment.

Standard: ISO 6330, GB/T8629-2017 Textiles - Household washing and drying procedures for experiments

Terms & Conditions:

1. 5.2.1 A1 Flip Dryer - Ventilated Type;
2. 10.2.1 Flip to dry
3. Appendix G Tumbling Dryer Type A1 Ventilated type
4. Appendix P with a timing device to flip the dryer for the determination of the drying time

Technical parameters

1. Test method: timing method, constant humidity method;
2. Category: front door feeding, horizontal drum type;
3. Number of lifting pieces: 3 pieces;
4. Drum diameter: 580mm±10mm;
5. Drum speed: 50r/min;
6. Controlled air outlet temperature: high temperature 75±5°C, low temperature less than 60°C;
7. Rated voltageFrequency: 220V . 50Hz;
8. Rated input power: 1850W;
9. Maximum current: 10A;
10. Rated capacity: 8 Kg of cotton clothing, 3Kg of chemical fiber clothing;
11. Dimensions (width × depth × height): 600mm×560mm×830mm;
12. Net weight: about 30kg;
13. Waterproof grade: IP×4;